



DON'T PAY

those high electricity bills ever again !



ORDERING CODE

SA Model No.	S-15
UL Model	ES-15
Specifications	208V, 15 kVAR, 3Φ, 4 wire, 60 Hz.
Product Code	8908004003053

TECHNICALS

Power Rating	15 kVAR	16.7 kVAR	20 kVAR
Voltage Rating	208V AC	220V AC	240V AC
Full Load Current	41 Amps.	44 Amps.	48 Amps.
Frequency	60 Hz.		
Operating Ambient	Upto 40°C		
Dimensions	20" x 20" (8" depth)		
Type	Type - 1, Wall Mounting		
Weight	34 Kg / 75 lbs		

ADVANTAGES

- 🌿 Reduction of Electric Bills.
- 🌿 Reduction in Demand charges.
- 🌿 Reduced Copper losses (I^2R losses)
- 🌿 Reduced core losses inductive loads.
- 🌿 Reduced electric breakdown
- 🌿 Surge suppression, long life of equipments.
- 🌿 Reduced carbon emission.
- 🌿 Incentive in electric bills in selected area.



- ✓ Recommended for 3Φ, 200 Amp & 400 Amp facility.
- ✓ Automatically generates capacitor combination to maintain power factor near to Unity. Individual control of each capacitor step.

kVAR each step (208V AC)					
STEPS →	1	2	3	4	5
kVAR	1	2	4	4	4

- ✓ Enhanced Capacitor Life, running at half the Rated Voltage.
- ✓ Controlled by Celec Digital Power Factor Regulator.
- ✓ Current sensor openable 400 Amp. Can be used with 1.25" cable.



CELEC Enterprises

12387 Silver Saddle Dr, Rancho Cucamonga, CA, 91739, USA
 Ph : +1-424-364-2640 Email : sales@celec.com

423, Industrial Area - A, Ludhiana - 141003, PB, INDIA
 Ph : +91-708-788-6330