



DON'T PAY

those high
electricity bills
ever again !



TECHNICALS

Power Rating	65 kVAr, 3 Phase
Voltage Rating	480V AC, 60Hz
Full Load Current	79 Amps.
Operating Ambient	Upto 40°C
Dimensions	24" x 30" (8" depth)
Type	Type - 1, Wall Mounting
Weight	59 Kg / 130 lbs

ADVANTAGES

- Reduction of Electric Bills.
- Reduction in Demand charges.
- Reduced Copper losses (I^2R losses)
- Reduced core losses inductive loads.
- Reduced electric breakdown
- Surge suppression, long life of equipments.
- Reduced carbon emission.
- Incentive in electric bills in selected area.

ORDERING CODE

Model	M-65
Specifications	480V, 65 kVAr, 3 ϕ , 3 wire, 60 Hz.
Product Code	



Commercial
Business



Casinos



Voltage
480V 3 ϕ 60 Hz

- Recommended for 3 ϕ , 400 Amp & 600 Amp facility.
- Power Factor sensing by current sensor, Suitable for main Incomer Cable.
- Automatically generates capacitor combination to maintain power factor unity.



Individual control of each capacitor

Capacitor Break-up

STEPS	1	2	3	4	5	6	7
kVAr	2	3	5	10	15	15	15

- Controlled by Inbuilt Digital Power Factor Regulator
- Enhanced Capacitor Life, as capacitors running at half the Rated Voltage.

CELEC Enterprises

12387 Silver Saddle Dr, Rancho Cucamonga, CA, 91739, USA
Ph : +1-424-364-2640 Email : sales@celec.com

423, Industrial Area - A, Ludhiana - 141003, PB, INDIA
Ph : +91-708-788-6330