



# DON'T PAY

those high  
electricity bills  
ever again !

## Description

- Smart capacitor bank with Auto Range Technology.
- Controlled by Celec digital regulator.
- Automatically generates capacitor combination to maintain power factor near to Unity.
- Over Current & short circuit protection.
- Main switch 63 amps with door lock protection.
- Current sensor 600 Amp clamp type included.

## Advantages

- Reduction of electric bills.
- Reduction in Demand charges.
- Reduced I R losses.
- Reduced core losses inductive loads.
- Reduced electric breakdown surge suppression for the long life of equipments.
- Reduced carbon emission.
- Incentive in electric bills in selected area.



## Suitable for:



SPECIFICATIONS	
Model no.	ES-9
Power Rating	9 kVAr
Rated Voltage	240V AC
Phase	1 Phase
Full Load Current	38 Amp.
No of Steps	9
Each Step kVAr	(0.36 X 2), (0.72 X 4), (2.17 X 3)
Frequency	50 Hz
Operating Ambient	10 C to 40 C
Humidity	Max. 95% (Non Condensing)
Cable Conductor	16 Sq. mm (MAIN) 0.5 Sq. mm (CT)
Dimensions	300mm(W) x 500mm(H) x 120mm(D)
Type	Wall Mounting