










# PRO-2000







**Subsidy Approved** 

An ISO 9001-2008 CERTIFIED COMPANY















## LASER KIT PRO-2000

Model	KIT PRO-2000
Range	1000 meters
Voltage Range	12 VDC±20%
Packing	Shock Proof ABS Plastic Body
Size	47cmx 39cm x 20.5cm
Weight	13 Kg.

#### Features:

- Range upto 1000 meters.
- Waterproof, dustproof to work all weather.
- High Temperature Level retain capability.
- Overvoltage and DC polarity protection.
- Low voltage safe working.
- One touch self-calibration infield.
- High power Laser beam
- All 12V System.

#### **ROTARY LASER**

ROTART LASER		
Model	PRO-2000	
Range	1000 mtr (Radius 500 mtr)	
Self Leveling Accuracy	± 1.5 mm @ 30 meters	
Rotating Speed	600 RPM (Fixed)	
Laser Diode (Type)	<5 mW, (Visible Red)	
Manual Kit	Upto ± 7 degree	
Battery	12V External	
Battery Life	72 Hours with full Charge	
Operating Temperature	0 to ± 50° C	
Storage Temperature	0 to ± 60° C	
Dust/Water Resistant	IP65	
Protection	Low Battery, Reverse Polarity	
Weight	2.5 Kg	
Dimensions	200 x 250 x 175 mm	
Remote Distance	Upto 100 meters	



#### **CONTROL BOX**

Model	Pro-touch	
Control	Combination of Touch, Lift Remote & Switch	
Display	Available Programmable	
Grade	Seven Segment LED, Visible in Day Light, Adjustable in Brightness	
Switch	Touch Sensor Switch Suitable for Dusty Condition	
System Accuracy	± 5 mm	
Protection	All Output Channels with short circuit Protection.	
Timer	Running Timer, Last Time, Total Working Hours	
Charge	For 12V Battery with Protection	
Working Indicator	Laser ON,LIN with Receiver,Auto,Manual,Up,Down	
Indications	Working Channel, Time & Errors (LED for Up, Down, Link & Auto)	
Protection	IP65	
Connectors	Silver coated, Chrome Plated all weather bend proof	
System Voltage	12 VDC	



## WIRE SET

Cable	Heavy Duty 1.5 sq mm make RR Kabel
Connector	Latest Avionics Grade Connector



### LASER RECIEVER

Model	PRO-Land	
Voltage Range	12 VDC±20%	
Max Current Consumption	200 mA	
System Accuracy	±5 mm Adjustable	
Laser Requirement	All rotating Lasers (HeNe or IR)	
Dust/Water Resistant	IP65	
Pulsed Display	10 Pulses per second	
Protection	Reverse Polarity	
Communication	1 Wire	
Weight	2 Kg	



#### **BATTERY CHARGER**

Section for the annual of the contract of the	
Model	CE-7AH
Input	230 VAC
Output	14V1A
Protection	2 kV



#### Parts of Laser Land Leveler



#### **Benefits of Laser Land Leveler**

- Optimization of water use efficiency
- Better crop establishment
- Reduction in irrigation time
- Less effort in crop management
- Laser leveled land with precision
- Reduces weed problems
- Improves uniformity of crop maturity
- Time efficiency in completion of task
- Easy land preparation
- Less water requirement for land preparation

































#### **CELEC USA**

12387 Silver Saddle Dr, Rancho Cucamonga, CA, 91739, USA Ph: +1-424-364-2640 Email: sales@celec.com

#### **CELEC INDIA**

423, Industrial Area - A, Ludhiana, PB - 141003, INDIA Ph: +91-708-788-6330 Email: sales@celec.com