CELEC
INSPIRED FOR ENERGY SAVING

UL LISTED

# Reduce your Home Electric Bills.




**3.3 kVAr**
Total capacity

**240 V**
Split-Phase, 60 Hz

**6 steps**
Individually controlled

**200 A**
Suitable facility

| MODEL | ES-1 |
|---|---|
| Full Load Current | 14.6 A |
| Operating ambient | Up to 104°F |
| Dimensions | 12" x 8" |
| Mounting | Type-1, Wall mounting |
| Weight Net/Gross | 13 / 15.5 lbs |
| Sensing | Split core Current Sensor |
| kVAr Steps | 0.11, 0.22, 0.33, (0.88 x 3) |

Auto-selects the optimal capacitor combinations.
Maintains target power factor in real time.
Individual switching of each capacitor.
Installs at the main panel in under 1 hr.

Controlled by Celec Digital Power Factor Regulator



- Reduced Electric Bills
- Lower Demand Charges
- AI Cloud Power Logger
- Surge Suppression
- Budget Friendly

**NECA 2026**
**Convention and Trade Show**
Las Vegas, Nevada.
October 4-7

**www.celec.com**

**CELEC Enterprises** | 423, Industrial Area - A, Ludhiana, PB - 141003, IN. | +1-424-364-2640 | E-mail : usa@celec.com

* Savings depend on utility tariffs and usage.